
How To Refinish Hardwood Floors

*How To Refinish
Hardwood Floors*

Downloaded from
old.oplm.com by Snyder
& Dayton

HOW TO REFINISH HARDWOOD FLOORS: A COMPLETE GUIDE TO RESTORING THEIR NATURAL BEAUTY

Hardwood floors add timeless warmth and value to any home. Over the years, however, even the best-maintained floors can show signs of wear—scratches, dullness, water marks, or fading. Instead of replacing them, refinishing offers a cost-effective way to bring back their original luster. Whether you are a seasoned DIYer or a first-timer, understanding **how to refinish hardwood floors** properly can save you thousands of dollars while giving your rooms a fresh, new look. This guide walks you through every step, from assessment to final finishing, using proven techniques and professional tips.

Before diving in, it is important to note that refinishing is a labor-intensive process that demands patience and attention to detail. However, the results are well worth the effort. In this article, we cover everything you need to know, including tools, preparation, sanding, staining, and applying the finish. By the end, you'll have the confidence to transform your tired flooring into a showstopper.

1. Assessing

Whether Your Hardwood Floors Need Refinishing

Not every worn floor requires full refinishing. Start by evaluating the condition of your hardwood. Look for deep scratches, stains that have penetrated the wood, or areas where the finish has worn down to bare wood. If the damage is only superficial—minor scuffs or light wear—a simple screening and recoat may suffice. However, if you see signs of water damage, cupping, or extensive scratches, a complete sand-and-refinish job is necessary.

Also check the thickness of the wood. Solid hardwood can usually be sanded multiple times over its lifespan. Engineered hardwood, on the other hand, has a thin top veneer that may only allow one or two refinishing passes. Use a small pry tool near a vent to measure the top layer. If it's less than 1/16 inch, refinishing might not be safe. In that case, consider recoating or replacing the boards.

Another critical factor is the age of the floor and the type of finish previously used. Older floors often have wax, shellac, or varnish that requires chemical stripping before sanding. If you're unsure, perform a small test in an inconspicuous area. Rub denatured alcohol on the surface: a softened finish indicates shellac; a sticky residue

suggests wax. Modern polyurethane will remain hard. Knowing the existing finish helps you choose the right approach for **how to refinish hardwood floors** effectively.

2. Gathering the Right Tools and Materials

Having the correct equipment makes the job smoother and safer. Below is a comprehensive list of what you will need:

- **Drum sander** (for the main floor area) and an **edger** (for corners and edges)
- A **random orbital sander** (for finer sanding or for engineered floors)
- **Sanding belts** in various grits: 36, 60, 80, and 100 (coarse to fine)
- **Sandpaper discs** for the edger (matching grits)
- **Shop vacuum** with a HEPA filter and a tack cloth for dust collection
- **Wood stain** (if you want to change the color) and **polyurethane finish** (water-based or oil-based)
- **Lambswool applicator** or high-quality brush for stain; a **paint tray** and **roller** for finish
- **Safety gear**: safety goggles, dust mask or respirator, ear protection, and work gloves
- **Wood filler** or putty for gaps, **nail punch**, **putty knife**, and **hammer**
- **Measuring tape**, **chalk line**, and **pry bar** for removing baseboards

- Protective sheets (plastic or canvas) to isolate the work area

Renting equipment from a home improvement store is cost-effective. Many rental centers also provide basic training on how to operate drum sanders and edgers. If you're tackling a large room, consider renting a floor buffer for buffing between coats. Investing in high-quality abrasives and finishes ensures a professional result.

3. Preparing the Room for Sanding

Preparation is key to a successful refinishing project. First, remove all furniture, rugs, and decorations from the room. If large pieces are too heavy, slide them onto a protected area in an adjoining room. Next, take off baseboards or shoe molding using a pry bar. This prevents damage and allows the sander to reach the floor edges. Label the pieces for easy reinstallation later.

Once the room is empty, inspect the floor closely. Use a hammer and nail punch to drive any protruding nail heads below the surface. Fill any cracks, gaps, or nail holes with a good quality wood filler that matches your wood species. Allow the filler to dry completely, then sand it flush with the surrounding floor. Also check for loose boards and secure them with finishing nails.

Finally, seal off the room with plastic sheeting and tape to contain dust. Close air vents and cover doorways. The sanding process generates fine powder that can travel throughout the house. A

shop vacuum with a HEPA filter will be your best friend during and after sanding. Thorough cleaning at this stage prevents scratches in the final finish.

4. Sanding the Hardwood Floors

Sanding is the most critical step when learning **how to refinish hardwood floors**. It removes the old finish and levels the wood surface. Start with a drum sander fitted with a coarse grit belt (36 or 40). Move in the direction of the wood grain at a steady, moderate pace. Do not stop the sander in one spot, as it creates dips. Overlap each pass by about half the width of the drum. For the first pass, angle the sander slightly (e.g., 45 degrees) to take down any unevenness, then follow with passes parallel to the grain.

After the coarse pass, switch to a 60-grit belt and repeat the same pattern. This intermediate sanding removes scratches left by the coarse grit. Then use an 80-grit belt for a smooth surface. Finally, a 100-grit belt gives a fine finish ready for stain or sealer. Remember to empty the dust bag frequently and change belts when they become dull.

Edges and corners require an edger—a handheld disc sander. Use the same progression of grits: 36, 60, 80, then 100. Be careful not to gouge the wood; keep the tool moving. For tight corners and under radiators, a detail sander or hand sanding with sandpaper will be necessary. After sanding, vacuum the entire floor thoroughly, then wipe down with a tack cloth to remove every trace of dust. For a flawless finish, you may want to do a final sand with a random orbital sander using 120-grit paper, then

vacuum again.

5. Staining Your Hardwood Floors (Optional)

If you wish to change the color of your floor, now is the time to apply stain. Choose a high-quality wood stain that penetrates evenly. Water-based stains dry faster and have lower VOCs, while oil-based stains offer richer colors but require longer drying times. Test the stain on a scrap piece of the same wood or an inconspicuous area to verify the hue.

Apply the stain using a lambswool applicator, brush, or clean rag. Work in manageable sections—about 3 to 4 feet wide—and always follow the grain. Let the stain sit for the manufacturer's recommended time (usually 5 to 15 minutes) then wipe off the excess with a clean cloth. For a darker color, you can apply a second coat after the first dries. Allow the stain to dry completely (check label instructions, often 24 hours) before applying the finish. Proper staining not only enhances the wood's natural beauty but also protects it.

6. Applying the Finish

The finish seals the wood and provides durability. The two most common options for hardwood floors are oil-based polyurethane and water-based polyurethane. Oil-based polyurethane gives a warm amber tone and is extremely durable, but it has strong

fumes and takes longer to dry (12-24 hours between coats). Water-based polyurethane dries clear, dries quickly (2-4 hours), and has low odor, making it a popular choice for modern homes. Both types perform well when applied correctly.

Before finishing, do a final vacuum and tack cloth wipe. Use a high-quality roller or lambswool applicator to apply a thin, even coat of polyurethane. Start at the farthest corner of the room and work toward the exit. Avoid bubbles by not overworking the finish. Allow the first coat to dry fully according to the product directions. Then lightly sand the surface with 220-grit sandpaper (using a pole sander or hand block) to remove any dust nibs. Vacuum and tack again.

Apply a second coat in the same manner. For best protection, a third coat is recommended, especially in high-traffic areas. Between coats, maintain a dust-free environment by closing windows and turning off fans if possible. After the final coat, let the floor cure for at least 72 hours (or as specified) before walking on it with soft shoes. Wait a full week before moving furniture back to avoid damaging the new finish.

7. Final Steps and Maintenance

Once the finish has fully cured, reinstall the baseboards and shoe molding. Touch up nail holes with filler and repaint if needed. Carefully move furniture back

into the room using felt pads under legs to prevent scratches. Place area rugs in high-traffic zones.

To keep your newly refinished hardwood floors looking great, follow a regular maintenance routine. Sweep or dust mop daily to remove grit that can scratch the surface. Use a microfiber mop and a cleaner specifically designed for hardwood. Avoid wet mopping or using wax-based products. Place doormats at entryways to trap dirt. Every few months, consider applying a refresher coat of polyurethane to high-wear areas. With proper care, your floors can stay beautiful for many years.

Conclusion

Learning **how to refinish hardwood floors** is a rewarding skill that can dramatically transform the look and feel of your home. From assessing the condition of your flooring to selecting the right tools, sanding meticulously, staining, and applying a durable finish, each step contributes to a professional result. While the process is time-consuming and demands careful attention, the outcome is a floor that looks brand new—at a fraction of the cost of replacement. Whether you choose to do it yourself or hire a professional, understanding the techniques ensures you make informed decisions. With the right preparation and execution, you can enjoy the beauty of your hardwood floors for decades to come.